

TCM GAFFELTRUCK OG RÆKKETRUCK, DIESEL FHD18Z7



MOTOR

Kapacitet: 5,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 8 timer, skift alle 200 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Kontroller alle 8 timer, skift alle 200 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 8 timer, skift alle 200 timer

TCM GAFFELTRUCK OG RÆKKETRUCK, DIESEL FHD18Z7



DIFFERENTIALE POWERSHIFT-VERSION

Kapacitet: 3,5 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Kontroller alle 600 timer, skift alle 1200 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	SP Gear 1081	SP Gear 5015

Kontroller alle 600 timer, skift alle 1200 timer

ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 600 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	SP Gear 1081	SP Gear 5015

Skift alle 600 timer

GEAR Powershift

Kapacitet: 7 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 10W	ATF Dexron II-D	

Kontroller alle 200 timer, skift alle 1200 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 10W	ATF Dexron II-D	

Kontroller alle 200 timer, skift alle 600 timer

TCM GAFFELTRUCK OG RÆKKETRUCK, DIESEL FHD18Z7



GEAR MANUEL

Kapacitet: 5,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Gearlube GL-5 80W-90

PRODUKTANBEFALING 3

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 600 timer, skift alle 1200 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 1081

PRODUKTANBEFALING 3

SP Gear 5015

Kontroller alle 600 timer, skift alle 1200 timer

HYDRAULISK SYSTEM

Kapacitet: 18 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

PRODUKTANBEFALING 2

Perlus H 32

PRODUKTANBEFALING 3

Perlus H 22

Kontroller alle 8 timer, skift alle 1200 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

PRODUKTANBEFALING 2

PRODUKTANBEFALING 3

Kontroller alle 8 timer, skift alle 1200 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

TCM GAFFELTRUCK OG RÆKKETRUCK, DIESEL FHD18Z7



KØLESYSTEM

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 8 timer, skift alle 24 måneder/ 600 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.