

# TCM GAFFELTRUCK OG RÆKKETRUCK, ELEKTRISK FHB20H4-VAN



## DIFFERENTIALE

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 1200 timer/ 12 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3 |
|--------------------------|---------------------|---------------------|
| <b>Agrifluid HT-Plus</b> | <b>SP Gear 1081</b> | <b>SP Gear 5015</b> |

Skift alle 1200 timer/ 12 måneder

## GEAR Powershift

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>SP Matic 2032</b> |  |  |

Skift alle 1200 timer/ 12 måneder

## GEAR MANUEL

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-4 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 1200 timer/ 12 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3 |
|--------------------------|---------------------|---------------------|
| <b>Agrifluid HT-Plus</b> | <b>SP Gear 1081</b> | <b>SP Gear 5015</b> |

Skift alle 1200 timer/ 12 måneder

## HYDRAULISK SYSTEM

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>Perlus H 32</b>  | <b>Perlus H 22</b>  |  |

Skift alle 1200 timer/ 12 måneder

# TCM GAFFELTRUCK OG RÆKKETRUCK, ELEKTRISK FHB20H4-VAN



## HYDRAULISK BREMSE- & KOBLINGSSYSTEM

| ANVEND                            |  | KLIMA   |
|-----------------------------------|--|---------|
| Normal                            |  | Moderat |
| PRODUKTANBEFALING 1               |  |         |
| <b>Drauliquid DOT 3</b>           |  |         |
| Skift alle 1200 timer/ 12 måneder |  |         |

## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## FINALEREDUKTIONSGEAR

| ANVEND                            |                                    | KLIMA            |
|-----------------------------------|------------------------------------|------------------|
| Normal                            |                                    | Middelhavsagtigt |
| PRODUKTANBEFALING 1               | PRODUKTANBEFALING 2                |                  |
| <b>Gearlube GL-4 80W-90</b>       | <b>Unigear HS GL-3/GL-5 80W-90</b> |                  |
| Skift alle 1200 timer/ 12 måneder |                                    |                  |

| ANVEND                            |                     | KLIMA               |
|-----------------------------------|---------------------|---------------------|
| Normal                            |                     | Moderat             |
| PRODUKTANBEFALING 1               | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3 |
| <b>Agrifluid HT-Plus</b>          | <b>SP Gear 1081</b> | <b>SP Gear 5015</b> |
| Skift alle 1200 timer/ 12 måneder |                     |                     |

## STYRETØJ

| ANVEND                            |                                    | KLIMA            |
|-----------------------------------|------------------------------------|------------------|
| Normal                            |                                    | Middelhavsagtigt |
| PRODUKTANBEFALING 1               | PRODUKTANBEFALING 2                |                  |
| <b>Gearlube GL-4 80W-90</b>       | <b>Unigear HS GL-3/GL-5 80W-90</b> |                  |
| Skift alle 1200 timer/ 12 måneder |                                    |                  |

| ANVEND                            |                     | KLIMA               |
|-----------------------------------|---------------------|---------------------|
| Normal                            |                     | Moderat             |
| PRODUKTANBEFALING 1               | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3 |
| <b>Agrifluid HT-Plus</b>          | <b>SP Gear 1081</b> | <b>SP Gear 5015</b> |
| Skift alle 1200 timer/ 12 måneder |                     |                     |

# TCM GAFFELTRUCK OG RÆKKETRUCK, ELEKTRISK FHB20H4-VAN



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*