

TEREX FUCHS ENTREPRENØRMASKINER MED HJUL MHL MHL354E DEUTZ TCD 6.1 L6 TIER 4I (354310/4001->) (2012 OG EFTER)



MOTOR Deutz TCD 6.1 L6
Kapacitet: 27 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	

Kontroller alle 8 timer, skift alle 12 måneder/ 500 timer

DIFFERENTIALE BAG
Kapacitet: 31 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 500 timer

DIFFERENTIALE FOR
Kapacitet: 31 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 500 timer

TEREX FUCHS ENTREPRENØRMASKINER MED HJUL MHL MHL354E DEUTZ TCD 6.1 L6 TIER 4I (354310/4001->) (2012 OG EFTER)



NAVREDUKTIONER BAG

Kapacitet: 1,8 liter (hvert nav)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer/ 12 måneder

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 500 timer

NAVREDUKTIONER FOR

Kapacitet: 1,8 liter (hvert nav)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer/ 12 måneder

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 500 timer

TEREX FUCHS ENTREPRENØRMASKINER MED HJUL MHL MHL354E DEUTZ TCD 6.1 L6 TIER 4I (354310/4001->) (2012 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 380 liter (Olieskiftskapacitet)

ANVEND		KLIMA
Fleksibel (max)		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus AF 46		

Kontroller alle 500 timer, skift alle 12 måneder/ 3000 timer

ANVEND		KLIMA
Fleksibel (max)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

Kontroller alle 500 timer, skift alle 12 måneder/ 3000 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie, fleksibel (maks.)		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 500 timer, skift alle 12 måneder/ 3000 timer

SMØREPUNKTER/NIPLER MIDTRE SMØRESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
HT Q9 High Grade Grease		

KØLESYSTEM

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SVINGREDUKTIONSENHED

Kapacitet: 6,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 1500 timer/ 12 måneder

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 500 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

TEREX FUCHS ENTREPRENØRMASKINER MED HJUL MHL MHL354E DEUTZ TCD 6.1 L6 TIER 4I (354310/4001->) (2012 OG EFTER)



Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.