

TEREX FUCHS OMLADEMASKINER MED LARVEBÅND RHL RHL331E DEUTZ TCD 4.1 L4 TIER 4I (331350/4001 ->)



MOTOR Deutz TCD 4.1 L4
Kapacitet: 16 liter

ANVEND

Normalt, svovlniveau i brændstof <0,05 %

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Agridiesel MSP 15W-40

Kontroller alle 8 timer, skift alle 12 måneder/ 500 timer

HYDRAULISK SYSTEM

Kapacitet: 900 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus AF 46

Skift alle 3000 timer/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46

Skift alle 3000 timer/ 12 måneder

ANVEND

Biologisk nedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

Skift alle 3000 timer/ 12 måneder

SMØREPUNKT / NIPLER RINGDREV

Kapacitet: 28 kg

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER MIDTRE SMØRESYSTEM

Kapacitet: 2 kg

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

TEREX FUCHS OMLADEMASKINER MED LARVEBÅND RHL RHL331E DEUTZ TCD 4.1 L4 TIER 4I (331350/4001 ->)



KØLESYSTEM

Kapacitet: 36 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

KØREREDUKTIONSENHED

Kapacitet: 5 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Gearlube GL-5 80W-90

PRODUKTANBEFALING 3

Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer/ 12 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Gearlube GL-5 80W-90

PRODUKTANBEFALING 3

Unigear HS GL-3/GL-5 80W-90

Skift alle 500 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.