

# TEREX FUCHS OMLADEMASKINER MED LARVEBÅND RHL RHL860D 860050/0016 -> 0018 (2011 OG EFTER)



## HYDRAULISK SYSTEM

Kapacitet: 520 liter (Hydrauliktank)

### ANVEND

Fleksibel (max)

### KLIMA

Middelhavsagtigt

### PRODUKTANBEFALING 1

**Perlus AF 46**

Skift alle 3000 timer/ 12 måneder

### ANVEND

Fleksibel (max)

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Perlus Biosynth 46**

### PRODUKTANBEFALING 2

**Perlus H 46**

Skift alle 3000 timer/ 12 måneder

### ANVEND

Alternativt, fleksibel (maks.)

### KLIMA

Middelhavsagtigt

### PRODUKTANBEFALING 1

**Perlus Biosynth 46**

Skift alle 3000 timer/ 12 måneder

## SMØREPUNKTER/NIPLER MIDTRE SMØRESYSTEM

Kapacitet: 4 kg

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**HT Q9 High Grade Grease**

## KØREREDUKTIONSENHED

Kapacitet: 5 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

Skift alle 500 timer/ 12 måneder

# TEREX FUCHS OMLADEMASKINER MED LARVEBÅND RHL RHL860D 860050/0016 -> 0018 (2011 OG EFTER)



## SVINGREDUKTIONSENHED

Kapacitet: 7 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 500 timer/ 12 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*