

# TEREX GRAVEMASKINER MED HJUL TW75 TCD 2.9 L4 TIER 4F (TW07540105 ->) (2015 OG EFTER)



**MOTOR** Deutz TCD 2.9 L4  
Kapacitet: 8 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP Ultra 10W-40**

PRODUKTANBEFALING 2

**Agrisynth LSP 10W-40**

PRODUKTANBEFALING 3

**Agridiesel MSP 15W-40**

*Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder*

## DIFFERENTIALE BAG

Kapacitet: 4,4 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Skift alle 1000 timer/ 12 måneder*

## DIFFERENTIALE FOR

Kapacitet: 4 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Skift alle 1000 timer/ 12 måneder*

## NAVREDUKTIONER BAG

Kapacitet: 0,9 liter (hvert nav)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Skift alle 1000 timer/ 12 måneder*

## NAVREDUKTIONER FOR

Kapacitet: 0,9 liter (hvert nav)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Skift alle 1000 timer/ 12 måneder*

# TEREX GRAVEMASKINER MED HJUL TW75 TCD 2.9 L4 TIER 4F (TW07540105 ->) (2015 OG EFTER)



## REDUKTIONSGEARKASSE

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube LS 80W-90**

*Skift alle 1000 timer/ 12 måneder*

## HYDRAULISK SYSTEM

Kapacitet: 180 liter (Hydrauliksystem inkl. tank), Kapacitet: 110 liter (Servicepåfyldning)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Perlus H 68**

*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Perlus Biosynth 46**

PRODUKTANBEFALING 2

**Perlus H 46**

PRODUKTANBEFALING 3

**Perlus Biosynth 32**

*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

ANVEND

Biologisk nedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

**Perlus Biosynth 46**

PRODUKTANBEFALING 2

**Perlus Biosynth 32**

*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

## SMØREPUNKTER/NIPLER

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

## KØLESYSTEM

Kapacitet: 15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant SP 15+**

PRODUKTANBEFALING 2

**Coolant SP 12**

PRODUKTANBEFALING 3

**Coolant -38 Organic NF**

*Kontroller alle 10 timer, skift alle 24 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*