

TEREX GRAVEMASKINER MED LARVEBÅND TC16 0885-> (2008 OG EFTER)



MOTOR Mitsubishi L3E

Kapacitet: 3,6 liter (Total), Filterkapacitet: 0,2 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SHPD 20W-50

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrisynth MSP 10W-40

PRODUKTANBEFALING 3

Agridiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SHPD 20W-50

Skift alle 100 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrisynth MSP 10W-40

PRODUKTANBEFALING 3

Agridiesel MSP 15W-40

Skift alle 100 timer

HYDRAULISK SYSTEM

Kapacitet: 25 liter (Hydrauliktank), Kapacitet: 35 liter (Total)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 68

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46

PRODUKTANBEFALING 3

Perlus Biosynth 32

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

TEREX GRAVEMASKINER MED LARVEBÅND TC16 0885-> (2008 OG EFTER)



ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 100 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32

Kontroller alle 100 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus Biosynth 32	

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

ANVEND		KLIMA
Første service, bionedbrydelig olie		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus Biosynth 32	

Kontroller alle 100 timer

SMØREPUNKTER/NIPLER		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 500 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 100 timer



TEREX GRAVEMASKINER MED LARVEBÅND TC16 0885-> (2008 OG EFTER)

**KØLESYSTEM**

Kapacitet: 4,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 12 måneder, skift alle 24 måneder***KØREREDUKTIONSENHED**

Kapacitet: 0,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90*Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90*Skift alle 100 timer***SVINGREDUKTIONSENHED**

Kapacitet: 0,1 liter

ANVEND

Fyldt på livstid

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.