

TEREX GRAVEMASKINER MED LARVEBÅND TC48 0100->0578 (2006-2008)



MOTOR Mitsubishi S4Q2

Kapacitet: 6,5 liter (Total), Filterkapacitet: 1 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Armado Synth 5W-30

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 100 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Skift alle 100 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Armado Synth 5W-30

Skift alle 100 timer

HYDRAULISK SYSTEM

Kapacitet: 72 liter (Hydrauliktank), Kapacitet: 102 liter (Total)

TEREX GRAVEMASKINER MED LARVEBÅND TC48 0100->0578 (2006-2008)



ANVEND Normal		KLIMA Middelhavsagtigt
PRODUKTANBEFALING 1 Perlus H 68		
<i>Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder</i>		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Perlus Biosynth 46	PRODUKTANBEFALING 2 Perlus H 46	PRODUKTANBEFALING 3 Perlus Biosynth 32
<i>Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder</i>		
ANVEND Første Service		KLIMA Middelhavsagtigt
PRODUKTANBEFALING 1 Perlus H 68		
<i>Kontroller alle 100 timer</i>		
ANVEND Første Service		KLIMA Moderat
PRODUKTANBEFALING 1 Perlus Biosynth 46	PRODUKTANBEFALING 2 Perlus H 46	PRODUKTANBEFALING 3 Perlus Biosynth 32
<i>Kontroller alle 100 timer</i>		
ANVEND Biologisk nedbrydelig olie		KLIMA Moderat
PRODUKTANBEFALING 1 Perlus Biosynth 46	PRODUKTANBEFALING 2 Perlus Biosynth 32	
<i>Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder</i>		
ANVEND Første service, bionedbrydelig olie		KLIMA Moderat
PRODUKTANBEFALING 1 Perlus Biosynth 46	PRODUKTANBEFALING 2 Perlus Biosynth 32	
<i>Kontroller alle 100 timer</i>		

TEREX GRAVEMASKINER MED LARVEBÅND TC48 0100->0578 (2006-2008)



SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 100 timer

KØLESYSTEM

Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 12 måneder, skift alle 24 måneder

KØREREDUKTIONSENHED

Kapacitet: 0,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 500 timer, skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 100 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.