

# TEREX WHEELED LOADERS TL65 0452->

## (2009 AND AFTER)



**ENGINE** Deutz D 2011 L04  
Capacity: 13 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 20W-50**

*Check every 10 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2

**Agrisynth MSP 10W-40**

PRODUCT RECOMMENDATION 3

**Agridiesel MSP 15W-40**

*Check every 10 hours, change every 1000 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 3,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Change every 100 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Change every 100 hours*

# TEREX WHEELED LOADERS TL65 0452->

## (2009 AND AFTER)



### HUB REDUCTIONS REAR

Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 100 hours*

### TRANSAXLE REAR

Capacity: 4-4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 100 hours*

### HYDRAULIC SYSTEM

Capacity: 40 liter (Change capacity), Capacity: 49 liter (Total)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus H 68***Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

PRODUCT RECOMMENDATION 2

**Perlus H 46**

PRODUCT RECOMMENDATION 3

**Perlus Biosynth 32***Check every 500 hours, change every 1000 hours/ 12 months*

# TEREX WHEELED LOADERS TL65 0452->

## (2009 AND AFTER)



USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		

*Check every 100 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	<b>Perlus Biosynth 32</b>

*Check every 100 hours*

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus Biosynth 32</b>	

*Check every 500 hours, change every 1000 hours/ 12 months*

USE		CLIMATE
Initial service, biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus Biosynth 32</b>	

*Check every 100 hours*

### HYDRAULIC BRAKE SYSTEM

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Check every 500 hours, change every 12 months/ 2000 hours*

# TEREX WHEELED LOADERS TL65 0452-> (2009 AND AFTER)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 500 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 100 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*