

TEREX LÆSSEMASKINER MED LARVEBÅND PT-60 (2008 OG EFTER)



MOTOR Perkins 404D-22T
Kapacitet: 10,6 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 6 måneder/ 250 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Synfleet SHPD 10W-40

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 6 måneder/ 250 timer

HYDRAULISK SYSTEM

Kapacitet: 30,3 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 32

Kontroller alle 10 timer, skift alle 500 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 10 timer

KØLESYSTEM

Kapacitet: 7,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.