

TEREX LEDDELTE LASTBILER MED TIPPELAD TA400 DETROIT DIESEL (A982) (2010 OG EFTER)



MOTOR Detroit Diesel Series 60
Kapacitet: 32 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

DIFFERENTIALE BAG BUGSERE
Kapacitet: 33 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

DIFFERENTIALE BAG FØRE
Kapacitet: 34 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

DIFFERENTIALE FOR
Kapacitet: 33 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

GEAR AUTOMATISK Allison 4500 ORS 6/1
Kapacitet: 61 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Kontroller alle 10 timer, skift alle 6000 timer

TEREX LEDDELTE LASTBILER MED TIPPELAD TA400 DETROIT DIESEL (A982) (2010 OG EFTER)



NAVREDUKTIONER BAG

Kapacitet: 9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

NAVREDUKTIONER FOR

Kapacitet: 9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

REDUKTIONSGEARKASSE

Kapacitet: 13 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

HYDRAULISK SYSTEM

Kapacitet: 330 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

PRODUKTANBEFALING 2

SP Matic 2032

PRODUKTANBEFALING 3

ATF Almirol

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

TEREX LEDDELTE LASTBILER MED TIPPELAD TA400 DETROIT DIESEL (A982) (2010 OG EFTER)



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SMØREPUNKTER/NIPLER DRIVAKSEL UNIVERSALLED

Kapacitet: 1,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 6 måneder/ 1000 timer

KØLESYSTEM MOTOR

Kapacitet: 67 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

KØLESYSTEM BREMSE

Kapacitet: 175 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 10W	HDX 10W	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.