

TEREX MINI-DUMPER PS4000H



MOTOR Kubota V2203
Kapacitet: 9,5 liter

ANVEND
Normal

KLIMA
Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 250 timer

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 250 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 10 timer, skift alle 250 timer

DIFFERENTIALE BAG
Kapacitet: 7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Agrifluid HT

Kontroller alle 250 timer, skift alle 500 timer

DIFFERENTIALE FOR
Kapacitet: 6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Agrifluid HT

Kontroller alle 250 timer, skift alle 500 timer

TEREX MINI-DUMPER PS4000H



HYDRAULISK SYSTEM

Kapacitet: 37 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 10 timer, skift alle 500 timer

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 10 timer, skift alle 500 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 50 timer

SMØREPUNKTER/NIPLER MIDTERSTE SVINGTAP

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

PRODUKTANBEFALING 2

Labora Grease

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.