

TEREX MINI-DUMPER PT2000 (2009 OG EFTER)



MOTOR Kubota D1703
Kapacitet: 7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 200 timer

DIFFERENTIALE BAG
Kapacitet: 4,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	Agrifluid HT	

Kontroller alle 250 timer, skift alle 500 timer

DIFFERENTIALE FOR
Kapacitet: 4,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	Agrifluid HT	

Kontroller alle 250 timer, skift alle 500 timer

GEAR
Kapacitet: 1,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 500 timer

REDUKTIONSGEARKASSE
Kapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 500 timer

TEREX MINI-DUMPER PT2000 (2009 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 37 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 10 timer, skift alle 500 timer

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Kontroller alle 10 timer, skift alle 500 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 50 timer

SMØREPUNKTER/NIPLER MIDTERSTE SVINGTAP

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

PRODUKTANBEFALING 2

Labora Grease

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.