

TEREX MOTORDREVNE VEJHØVLE TG150-A (2007 OG EFTER)



MOTOR Cummins QSB6.7
Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Middelhavssagtigt

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Synfleet SHPD 10W-40

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

AKSELGEAR BAGAKSEL
Kapacitet: 13,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140

Skift alle 500 timer

DIFFERENTIALE FOR
Kapacitet: 8,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140

Skift alle 500 timer

TEREX MOTORDREVNE VEJHØVLE TG150-A (2007 OG EFTER)



GEAR ZF 6WG160 6/2
Kapacitet: 34 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Kontroller alle 50 timer, skift alle 1000 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Synfleet SHPD 10W-40

PRODUKTANBEFALING 2
Multifleet SHPD 10W-40

Kontroller alle 50 timer, skift alle 1000 timer

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
ATF-A

Kontroller alle 50 timer, skift alle 1000 timer

NAVREDUKTIONER BAG
Kapacitet: 4 liter (hvert)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube Racing 75W-140

PRODUKTANBEFALING 2
Gearlube LS 80W-90

PRODUKTANBEFALING 3
Unigear LS GL-3/GL-5 85W-140

Skift alle 500 timer

NAVREDUKTIONER FOR
Kapacitet: 1,8 liter (hvert)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube Racing 75W-140

PRODUKTANBEFALING 2
Gearlube LS 80W-90

PRODUKTANBEFALING 3
Unigear LS GL-3/GL-5 85W-140

Skift alle 500 timer

TEREX MOTORDREVNE VEJHØVLE TG150-A (2007 OG EFTER)



TANDEMREVENHED BAGAKSEL

Kapacitet: 21 liter (hvert)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube Racing 75W-140	Gearlube LS 80W-90	Unigear LS GL-3/GL-5 85W-140

Kontroller alle 500 timer, skift alle 30 måneder/ 4000 timer

HYDRAULISK SYSTEM

Kapacitet: 170 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus H 68	Perlus AF 68	Perlus AF 100

Kontroller alle 50 timer, skift alle 30 måneder/ 3000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus AF 46	

Kontroller alle 50 timer, skift alle 30 måneder/ 3000 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 22	Perlus AF 32	

Kontroller alle 50 timer, skift alle 30 måneder/ 3000 timer

SMØREPUNKTER/NIPLER

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KØLESYSTEM

Kapacitet: 33 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Kontroller alle 50 timer

TEREX MOTORDREVNE VEJHØVLE TG150-A (2007 OG EFTER)



ROTATIONSMEKANISME BLAD

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 500 timer, skift alle 30 måneder/ 4000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.