

TEREX SPOREDE SKOVANHÆNGERE

TEREXLIFT TX 110-72R



MOTOR

Kapacitet: 12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 250 timer

DIFFERENTIALE BAG

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

DIFFERENTIALE FOR

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

NAVREDUKTIONER BAG

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

NAVREDUKTIONER FOR

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

TEREX SPOREDE SKOVANHÆNGERE

TEREXLIFT TX 110-72R



REDUKTIONSGEARKASSE

Kapacitet: 2,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 200 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

Kontroller alle 10 timer, skift alle 1000 timer

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

Skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 32 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer

TEREX SPOREDE SKOVANHÆNGERE

TEREXLIFT TX 110-72R



SVINGREDUKTIONSENHED

Kapacitet: 2,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.