

# TEREX TEREXLIFT TB50 DEUTZ F3L1011 (2001 OG EFTER)



**MOTOR** Deutz F3L-1011  
Kapacitet: 4-5,5 liter

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1  
**Multifleet SHPD 20W-50**

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

PRODUKTANBEFALING 1  
**Kroontrak CVT 10W-40**

PRODUKTANBEFALING 2  
**Helar 0W-40**

PRODUKTANBEFALING 3  
**Agridiesel CRD+ 15W-40**

**PLANETGEAR**  
Kapacitet: 1,25 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

PRODUKTANBEFALING 1  
**Gearlube GL-4 80W-90**

PRODUKTANBEFALING 2  
**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 1000 timer/ 12 måneder*

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Første Service | Moderat |

PRODUKTANBEFALING 1  
**Gearlube GL-4 80W-90**

PRODUKTANBEFALING 2  
**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 50 timer*

**HYDRAULISK SYSTEM**  
Kapacitet: 144 liter (Hydrauliktank)

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

PRODUKTANBEFALING 1  
**SP Matic 2032**

PRODUKTANBEFALING 2  
**ATF Almirol**

*Kontroller alle 10 timer*

|                         |         |
|-------------------------|---------|
| ANVEND                  | KLIMA   |
| Alternativ (acceptabel) | Moderat |

PRODUKTANBEFALING 1  
**Perlus H 32**

PRODUKTANBEFALING 2  
**Perlus AF 32**

*Kontroller alle 10 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.