

TEREX TEREXLIFT TB60 CUMMINS 4B3.7 (2001 OG EFTER)



MOTOR Cummins 4B3.7
Kapacitet: 4-5,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet CD+ 15W-40

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1		
Multifleet SHPD 15W-40		

PLANETGEAR
Kapacitet: 1,25 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 50 timer

HYDRAULISK SYSTEM
Kapacitet: 197 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 10 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 10 timer

TEREX TEREXLIFT TB60 CUMMINS 4B3.7 (2001 OG EFTER)



KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.