

# THALER GUMMIHJULSLÆSSERE 4061/A



**MOTOR** Perkins 404D-22T  
Kapacitet: 9,5 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           |
|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Kontroller alle 10 timer, skift alle 400 timer/ 12 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           |
|-------------------------------|-------------------------------|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 10W-40</b> |

Kontroller alle 10 timer, skift alle 400 timer/ 12 måneder

**DIFFERENTIALE BAG**  
Kapacitet: 5,1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1       |  |
|---------------------------|--|
| <b>Gearlube LS 80W-90</b> |  |

Skift alle 400 timer/ 12 måneder

**DIFFERENTIALE FOR**  
Kapacitet: 4,4 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Skift alle 400 timer/ 12 måneder

**HYDRAULISK SYSTEM**  
Kapacitet: 56 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1       | PRODUKTANBEFALING 2 |
|---------------------------|---------------------|
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>  |

Kontroller alle 10 timer, skift alle 1200 timer/ 24 måneder

**HYDRAULISK BREMSESYSTEM**

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Perlus H 15****SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2****KØLESYSTEM**

Kapacitet: 13 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant SP 15+**

PRODUKTANBEFALING 2

**Coolant SP 12**

PRODUKTANBEFALING 3

**Coolant -38 Organic NF***Kontroller alle 10 timer, skift alle 24 måneder/ 3000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*