

THALER TELESKOPISK GRAVER 3150/TA



MOTOR Perkins 404D-22
Kapacitet: 9,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 400 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 400 timer/ 12 måneder

DIFFERENTIALE BAG
Kapacitet: 4,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Gearlube LS 80W-90	

Skift alle 400 timer/ 12 måneder

DIFFERENTIALE FOR
Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 400 timer/ 12 måneder

HYDRAULISK SYSTEM
Kapacitet: 36 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Perlus Biosynth 46	Perlus H 46

Kontroller alle 10 timer, skift alle 1200 timer/ 24 måneder

THALER TELESKOPISK GRAVER 3150/TA



HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 15		

SMØREPUNKTER/NIPLER

Kapacitet: 0,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 13 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 24 måneder/ 3000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.