

TOYOTA GAFFELTRUCKS, LP-GAS/BENZIN 50-8FG25 (2007 OG EFTER)



MOTOR Toyota 4Y
Kapacitet: 4 liter

ANVEND

Forlænget

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Kontroller alle 10 timer, skift alle 500 timer

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 250 timer

DIFFERENTIALE

Kapacitet: 5,8-6,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 2000 timer/ 12 måneder

GEAR

Kapacitet: 6 liter, Kapacitet: 10 liter (2 stator T/C)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 40 timer, skift alle 6 måneder/ 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 33 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

Kontroller alle 40 timer, skift alle 6 måneder/ 1000 timer

TOYOTA GAFFELTRUCKS, LP-GAS/BENZIN 50-8FG25 (2007 OG EFTER)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0,2 liter (Tank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 8 timer, skift alle 6 måneder/ 1000 timer

VÅDBREMSESYSTEM

Kapacitet: 8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3

Agrifluid HT-Plus

Kontroller alle 8 timer, skift alle 6 måneder/ 1000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

Skift alle 40 timer/ 1 hvert løb

KØLESYSTEM

Kapacitet: 8,1-9,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.