

TOYOTA GAFFELTRUCKS, LP-GAS/BENZIN TONERO 30 (2009 OG EFTER)



MOTOR Toyota 4Y
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Kontroller alle 8 timer, skift alle 3 måneder/ 500 timer

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

Kontroller alle 8 timer, skift alle 6 uger/ 250 timer

DIFFERENTIALE

Kapacitet: 8,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Gearlube GL-5 80W-90

PRODUKTANBEFALING 3

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 6 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

GEAR + MOMENTOMFORMER

Kapacitet: 6-10 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 40 timer, skift alle 12 måneder/ 2000 timer

HYDRAULISK SYSTEM

Kapacitet: 34 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 32

Kontroller alle 8 timer, skift alle 6 måneder/ 1000 timer

TOYOTA GAFFELTRUCKS, LP-GAS/BENZIN TONERO 30 (2009 OG EFTER)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0,2 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 8 timer, skift alle 6 måneder/ 1000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

Skift alle 40 timer/ 1 hvert løb

SMØREPUNKTER/NIPLER HJULLEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

Skift alle 1000 timer/ 6 måneder

KØLESYSTEM

Kapacitet: 9,28 liter, Kapacitet: 0,47 liter (Tank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.