

VALMET (KOMATSU FOREST) SPEDITØRER 890-1 310091>



MOTOR		
ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	

DIFFERENTIALE BOGIE-AKSEL		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

DIFFERENTIALE FOR 6-HJULSTRÆKKER		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

OVERFØRSELSKASSE BEGRÆNSET SLIP		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

PLANETREDUKTIONSENHED 6-HJULSTRÆKKER		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

REDUKTIONSGEARKASSE		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

VALMET (KOMATSU FOREST) SPEDITØRER 890-1 310091>



BOGIE-HUS		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HYDRAULISK SYSTEM		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

SMØREPUNKTER/NIPLER		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -33 MPG		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.