

# VENIERI RENDEGRAVER VF 10.23 PERKINS 1104C-44T



**MOTOR** Perkins 1104C-44T  
Kapacitet: 9,75 liter

| ANVEND                        |                               | KLIMA   |
|-------------------------------|-------------------------------|---------|
| Normal                        |                               | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           |         |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |         |

*Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder*

**DIFFERENTIALE BAG**  
Kapacitet: 9 liter

| ANVEND                      |                                  | KLIMA                    |
|-----------------------------|----------------------------------|--------------------------|
| Normal                      |                                  | Moderat                  |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2              | PRODUKTANBEFALING 3      |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

*Kontroller alle 200 timer, skift alle 1000 timer*

**DIFFERENTIALE FOR**  
Kapacitet: 9 liter

| ANVEND                      |                                  | KLIMA                    |
|-----------------------------|----------------------------------|--------------------------|
| Normal                      |                                  | Moderat                  |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2              | PRODUKTANBEFALING 3      |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

*Kontroller alle 200 timer, skift alle 1000 timer*

**GEAR HYDROSTATISK** Bosch Hydromatic 4/4  
Kapacitet: 1,7 liter

| ANVEND                      |                                  | KLIMA                    |
|-----------------------------|----------------------------------|--------------------------|
| Normal                      |                                  | Moderat                  |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2              | PRODUKTANBEFALING 3      |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

*Kontroller alle 200 timer, skift alle 1000 timer*

**NAVREDUKTIONER BAG**  
Kapacitet: 1,4 liter (hver (2x))

| ANVEND                      |                                  | KLIMA                    |
|-----------------------------|----------------------------------|--------------------------|
| Normal                      |                                  | Moderat                  |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2              | PRODUKTANBEFALING 3      |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

*Kontroller alle 200 timer, skift alle 1000 timer*

# VENIERI RENDEGRAVER VF 10.23 PERKINS 1104C-44T



## NAVREDUKTIONER FOR

Kapacitet: 0,9 liter (hver (2x))

| ANVEND                      |                                  | KLIMA                    |
|-----------------------------|----------------------------------|--------------------------|
| Normal                      |                                  | Moderat                  |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2              | PRODUKTANBEFALING 3      |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

Kontroller alle 200 timer, skift alle 1000 timer

## HYDRAULISK SYSTEM

Kapacitet: 126 liter

| ANVEND                      |                                  | KLIMA                    |
|-----------------------------|----------------------------------|--------------------------|
| Normal                      |                                  | Moderat                  |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2              | PRODUKTANBEFALING 3      |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

## HYDRAULISK BREMSESYSYSTEM

Kapacitet: 2 liter

| ANVEND              |                     | KLIMA   |
|---------------------|---------------------|---------|
| Normal              |                     | Moderat |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |         |
| <b>ATF-A</b>        | <b>Perlus H 15</b>  |         |

## SMØREPUNKTER/NIPLER GENERELT

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 24 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.