

# VOLVO GRAVEMASKINER MED LARVEBÅND EC EC140D STAGE IIIB/TIER 4I (2012-2017)



**MOTOR** Volvo D4H Tier 4i  
Kapacitet: 16 liter

| ANVEND                          | KLIMA   |
|---------------------------------|---------|
| Svovlniveau i brændstof <15 ppm | Moderat |

| PRODUKTANBEFALING 1                 | PRODUKTANBEFALING 2               | PRODUKTANBEFALING 3         |
|-------------------------------------|-----------------------------------|-----------------------------|
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> |

Kontroller alle 8 timer, skift alle 500 timer

| ANVEND                                       | KLIMA   |
|----------------------------------------------|---------|
| Alternativt, svovlniveau i brændstof <15 ppm | Moderat |

| PRODUKTANBEFALING 1                 | PRODUKTANBEFALING 2               | PRODUKTANBEFALING 3         |
|-------------------------------------|-----------------------------------|-----------------------------|
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> |

Kontroller alle 8 timer, skift alle 250 timer

**HYDRAULISK SYSTEM**  
Kapacitet: 250 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>Perlus H 46</b>  | <b>Perlus H 68</b>  |  |

Skift alle 2000 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 32</b>  |  |  |

Skift alle 2000 timer

| ANVEND                     | KLIMA            |
|----------------------------|------------------|
| Biologisk nedbrydelig olie | Middelhavsagtigt |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

Skift alle 5000 timer

**SMØREPUNKTER/NIPLER**

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1     |  |  |
|-------------------------|--|--|
| <b>MoS2 Grease EP 2</b> |  |  |

# VOLVO GRAVEMASKINER MED LARVEBÅND EC EC140D STAGE IIIB/TIER 4I (2012-2017)



## KØLESYSTEM

Kapacitet: 14 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant SP 15+**

### PRODUKTANBEFALING 2

**Coolant SP 12**

*Skift alle 6000 timer*

## KØREREDUKTIONSENHED

Kapacitet: 2,2 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

### PRODUKTANBEFALING 3

**Gearlube HS GL-5 80W-140**

*Skift alle 2000 timer*

### ANVEND

Første Service

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

### PRODUKTANBEFALING 3

**Gearlube HS GL-5 80W-140**

*Skift alle 500 timer*

## SVINGKRANS GEARBAD

Kapacitet: 9 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

### PRODUKTANBEFALING 3

**Gearlube HS GL-5 80W-140**

*Skift alle 1000 timer*

# VOLVO GRAVEMASKINER MED LARVEBÅND EC EC140D STAGE IIIB/TIER 4I (2012-2017)

**SVINGREDUKTIONSENHED**

Kapacitet: 3,9 liter

**ANVEND**

Normal

**KLIMA**

Moderat

**PRODUKTANBEFALING 1****Gearlube GL-5 80W-90****PRODUKTANBEFALING 2****Unigear HS GL-3/GL-5 80W-90****PRODUKTANBEFALING 3****Gearlube HS GL-5 80W-140***Skift alle 2000 timer***ANVEND**

Første Service

**KLIMA**

Moderat

**PRODUKTANBEFALING 1****Gearlube GL-5 80W-90****PRODUKTANBEFALING 2****Unigear HS GL-3/GL-5 80W-90****PRODUKTANBEFALING 3****Gearlube HS GL-5 80W-140***Skift alle 500 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*