

VOLVO GRAVEMASKINER MED LARVEBÅND EC EC15B (2002-2010)



MOTOR Volvo D1D
Kapacitet: 3,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

Skift alle 250 timer/ 12 måneder

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

Skift alle 50 timer

HYDRAULISK SYSTEM
Kapacitet: 33 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Perlus H 68

Skift alle 1000 timer/ 12 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus Biosynth 46

PRODUKTANBEFALING 2
Perlus H 46

Skift alle 1000 timer/ 12 måneder

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
Perlus H 32

Skift alle 1000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

VOLVO GRAVEMASKINER MED LARVEBÅND EC EC15B (2002-2010)

**KØLESYSTEM**

Kapacitet: 4,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Skift alle 3000 timer/ 12 måneder***SPORREDUKTIONSGEARKASSE**

Kapacitet: 0,33 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 1000 timer/ 12 måneder***SPORRULLER & MELLEMHJUL**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.