

VOLVO GRAVEMASKINER MED LARVEBÅND EC EC20C TIER 4I (2010-2015)



MOTOR Volvo D1.1DCAE4
Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30

Kontroller alle 8 timer, skift alle 250 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 15 liter (Hydrauliktank), Kapacitet: 25 liter (Total)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Perlus Biosynth 46	Perlus H 46	Perlus H 68

Kontroller alle 8 timer, skift alle 1000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 32	Perlus H 32	

Kontroller alle 8 timer, skift alle 1000 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 8 timer, skift alle 750 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1		
Perlus Biosynth 32		

Kontroller alle 8 timer, skift alle 750 timer

VOLVO GRAVEMASKINER MED LARVEBÅND EC EC20C TIER 4I (2010-2015)

**KØLESYSTEM**

Kapacitet: 5,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12*Kontroller alle 8 timer, skift alle 2000 timer***KØREREDUKTIONSENHED**

Kapacitet: 0,33 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140*Skift alle 1000 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.