

VOLVO GRAVEMASKINER MED LARVEBÅND EC EC235D STAGE IIIB/TIER 4I (2012-2014)



MOTOR Volvo D6H Tier 4i
Kapacitet: 32 liter

ANVEND	KLIMA
Svovlniveau i brændstof <15 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Kontroller alle 8 timer, skift alle 500 timer

ANVEND	KLIMA
Alternativt, svovlniveau i brændstof <15 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Kontroller alle 8 timer, skift alle 250 timer

HYDRAULISK SYSTEM
Kapacitet: 300 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 68	

Skift alle 2000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 32		

Skift alle 2000 timer

ANVEND	KLIMA
Biologisk nedbrydelig olie	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Skift alle 5000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

VOLVO GRAVEMASKINER MED LARVEBÅND EC EC235D STAGE IIIB/TIER 4I (2012-2014)



KØLESYSTEM

Kapacitet: 41 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 6000 timer

KØREREDUKTIONSENHED

Kapacitet: 5,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

PRODUKTANBEFALING 3

Gearlube HS GL-5 80W-140

Skift alle 2000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

PRODUKTANBEFALING 3

Gearlube HS GL-5 80W-140

Skift alle 500 timer

SVINGKRANS GEARBAD

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

PRODUKTANBEFALING 3

Gearlube HS GL-5 80W-140

Skift alle 1000 timer

VOLVO GRAVEMASKINER MED LARVEBÅND EC EC235D STAGE IIIB/TIER 4I (2012-2014)

**SVINGREDUKTIONSENHED**

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

PRODUKTANBEFALING 3

Gearlube HS GL-5 80W-140*Skift alle 2000 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

PRODUKTANBEFALING 3

Gearlube HS GL-5 80W-140*Skift alle 500 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.