

VOLVO GUMMIHJULSLÆSSERE L L20F

VOLVO D3.6D STAGE IIIA/TIER 3 (2010-2013)



MOTOR Volvo D3.6D
Kapacitet: 10,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Kontroller alle 8 timer, skift alle 1000 timer

DIFFERENTIALE FOR
Kapacitet: 4,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 1500 timer

SELVSPÆRRENDE DIFFERENTIALE FOR
Kapacitet: 4,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Gearlube LS 80W-90	

Skift alle 1500 timer

TRANSAKSEL BAG MED SPÆRDIFFERTIALE
Kapacitet: 5,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Gearlube LS 80W-90	

Skift alle 1500 timer

TRANSAKSEL BAG-
Kapacitet: 5,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 1500 timer

VOLVO GUMMIHJULSLÆSSERE L L20F

VOLVO D3.6D STAGE IIIA/TIER 3 (2010-2013)



HYDRAULISK SYSTEM

Kapacitet: 60 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 68

Skift alle 1500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 32

Skift alle 1500 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 1500 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Skift alle 1500 timer

ANVEND	KLIMA
Biologisk nedbrydelig olie	Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

Skift alle 1500 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth LSP 10W-40

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.