

VOLVO GUMMIHJULSLÆSSERE L L45F (2009-2011)



MOTOR Volvo D5D CAE3 Stage IIIA/Tier 3
Kapacitet: 16 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Armado Synth LSP Ultra 5W-30

Kontroller alle 8 timer, skift alle 500 timer

DIFFERENTIALE BAG

Kapacitet: 18,7 liter (+ Transferegearkasse)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 1000 timer

DIFFERENTIALE FOR

Kapacitet: 17,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 1000 timer

REDUKTIONSGEARKASSE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Skift alle 1000 timer

VOLVO GUMMIHJULSLÆSSERE L L45F

(2009-2011)



HYDRAULISK SYSTEM

Kapacitet: 95 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

PRODUKTANBEFALING 3

Multifleet SCD 30*Skift alle 1500 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Perlus Biosynth 32

PRODUKTANBEFALING 3

Perlus H 32*Skift alle 1500 timer*

ANVEND

Biologisk nedbrydelig olie

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus Biosynth 46*Skift alle 1500 timer*

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 20 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12*Kontroller alle 8 timer, skift alle 6000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.