

VOLVO GUMMIHJULSLÆSSERE L L70G STAGE IIIB/TIER 4I (2012-2015)



MOTOR Volvo D6H Tier 4i
Kapacitet: 18 liter

ANVEND

Svovlniveau i brændstof <15 ppm

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth MSP 10W-40

Kontroller alle 8 timer, skift alle 500 timer

ANVEND

Alternativt, svovlniveau i brændstof <15 ppm

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth MSP 10W-40

Kontroller alle 8 timer, skift alle 250 timer

DIFFERENTIALE BAG AWB 20
Kapacitet: 31 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

Skift alle 2000 timer

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Agrifluid HT

Skift alle 1000 timer

DIFFERENTIALE FOR AWB 25
Kapacitet: 38 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

Skift alle 2000 timer

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

Agrifluid HT

Skift alle 1000 timer

VOLVO GUMMIHJULSLÆSSERE L L70G

STAGE IIIB/TIER 4I (2012-2015)



GEAR Volvo HTE 125
Kapacitet: 20 liter

ANVEND		KLIMA
Alternativ (acceptabel)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Skift alle 2000 timer

HYDRAULISK SYSTEM
Kapacitet: 135 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus H 68		

Skift alle 4000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

Skift alle 4000 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

KØLESYSTEM
Kapacitet: 38 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	

Skift alle 48 måneder/ 6000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.