

VOLVO RENDEGRAVER BL BL71B (2011-2015)



MOTOR Volvo D5D CAE3 Stage IIIA/Tier 3
Kapacitet: 14-15 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Kontroller alle 8 timer, skift alle 500 timer

DIFFERENTIALE BAG

Kapacitet: 14,5 liter (+ navreduktioner)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid HT-Plus	Agrifluid HT	

Skift alle 1000 timer

DIFFERENTIALE FOR

Kapacitet: 6,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid HT-Plus	Agrifluid HT	

Skift alle 1000 timer

GEAR Powershift 4/4

Kapacitet: 14-16 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid HT-Plus	Agrifluid HT	

Skift alle 2000 timer

GEAR PowerShuttle 4/4

Kapacitet: 14-16 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid HT-Plus	Agrifluid HT	

Skift alle 2000 timer

VOLVO RENDEGRAVER BL BL71B (2011-2015)



NAVREDUKTIONER BAG

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid HT-Plus	Agrifluid HT	
<i>Skift alle 1000 timer</i>		

NAVREDUKTIONER FOR Kapacitet: 0,8 liter (hvert nav)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid HT-Plus	Agrifluid HT	
<i>Skift alle 1000 timer</i>		

HYDRAULISK SYSTEM Kapacitet: 39 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus H 68		
<i>Kontroller alle 8 timer, skift alle 1000 timer</i>		

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 32	
<i>Kontroller alle 8 timer, skift alle 1000 timer</i>		

KØLESYSTEM Kapacitet: 22 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15+	Coolant SP 12	
<i>Kontroller alle 8 timer, skift alle 6000 timer</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.