

VOLVO TROMLEMASKINER PÅ HJUL MW MW500 GFT 9T2 (2007-2014)



MOTOR Deutz TCD 2012 L04 2V
Kapacitet: 10 liter, Filterkapacitet: 1,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Armado Synth LSP Ultra 10W-40

Skift alle 500 timer

ANVEND	KLIMA
Alternativ (acceptabel)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Skift alle 500 timer

GEAR
Kapacitet: 4 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

HYDRAULISK SYSTEM
Kapacitet: 68 liter (Hydrauliktank), Kapacitet: 75 liter (System)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

KØLESYSTEM
Kapacitet: 15 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Coolant -38 Organic NF	Coolant -26

Skift alle 1000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.