

WACKER NEUSON GRAVEMASKINER MED LARVEBÅND 50Z3 YANMAR 4TNV88-PNS TIER 2 (-> AD07125)



MOTOR Yanmar 4TNV88-PNS
Kapacitet: 7,8 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Skift alle 500 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Kroontrak CVT 10W-40

Skift alle 500 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 500 timer

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Kroontrak CVT 10W-40

Skift alle 50 timer

WACKER NEUSON GRAVEMASKINER MED LARVEBÅND 50Z3 YANMAR 4TNV88-PNS TIER 2 (-> AD07125)



ANVEND		KLIMA
Første Service		Koldt
PRODUKTANBEFALING 1		
Multifleet SCD 10W		
Skift alle 50 timer		

HYDRAULISK SYSTEM Kapacitet: 80 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	
Skift alle 1000 timer/ 12 måneder		

ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		
Skift alle 1000 timer/ 12 måneder		

SMØREPUNKTER/NIPLER		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

KØLESYSTEM Kapacitet: 7 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Skift alle 1000 timer/ 12 måneder		

WACKER NEUSON GRAVEMASKINER MED LARVEBÅND 50Z3 YANMAR 4TNV88-PNS TIER 2 (-> AD07125)

**KØREREDUKTIONSENHED**

Kapacitet: 1,3 liter (hvert)

ANVEND

Normal, <- 10/2006

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 1000 timer/ 12 måneder*

ANVEND

Normal, 10/2006 ->

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 1000 timer/ 12 måneder*

ANVEND

Indledende service, <- 10/2006

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 50 timer*

ANVEND

Indledende service, 10/2006 ->

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 50 timer***SVINGKRANS FORTANDING**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 2

MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.