

WEIDEMANN GUMMIHJULSLÆSSERE 1230

P33 (1999-2003)



MOTOR Perkins 403C-15
Kapacitet: 5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2
Multifleet SHPD 15W-40

DIFFERENTIALE BAG
Kapacitet: 1,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

DIFFERENTIALE FOR
Kapacitet: 1,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

REDUKTIONSGEARKASSE
Kapacitet: 0,75 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

SELVSPÆRRENDE DIFFERENTIALE BAG

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

WEIDEMANN GUMMIHJULSLÆSSERE 1230

P33 (1999-2003)



SELVSPÆRRENDE DIFFERENTIALE FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

HYDRAULISK SYSTEM HYDROSTATISK DREV

Kapacitet: 26,5 liter, Kapacitet: 18 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus AF 46

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 7,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.