

WEIDEMANN GUMMIHJULSLÆSSERE 3070 CX60 DEUTZ D2011 L04W (2006-2008)



MOTOR Deutz D 2011 L04W
Kapacitet: 10,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SHPD 20W-50

Skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrisynth MSP 10W-40

PRODUKTANBEFALING 3

Agridiesel MSP 15W-40

Skift alle 1000 timer/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 4,9 liter, Kapacitet: 6,1 liter (30 km/t version)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

DIFFERENTIALE FOR

Kapacitet: 4,2 liter, Kapacitet: 5,2 liter (30 km/t version)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

HYDRAULISK SYSTEM

Kapacitet: 100 liter (Hydrauliksystem inkl. tank), Kapacitet: 80 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus AF 46

WEIDEMANN GUMMIHJULSLÆSSERE 3070 CX60 DEUTZ D2011 L04W (2006-2008)



HYDRAULISK BREMSESYSTEM

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 10 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.