

WERKLUST GUMMIHJULSLÆSSERE WG

WG 17E CUMMINS QSB 4.5



MOTOR Cummins QSB4.5

Kapacitet: 16,4 liter, Filterkapacitet: 2,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Skift alle 250 timer

DIFFERENTIALE BAG ZF MT-3065 BKV

Kapacitet: 24,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 100 timer, skift alle 1000 timer

DIFFERENTIALE FOR ZF MT-3065 CK

Kapacitet: 24,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 100 timer, skift alle 1000 timer

GEAR POWERSHIFT ZF 4WG130 4/3

Kapacitet: 9 liter (Servicepåfyldning), Kapacitet: 17 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 1000 timer

WERKLUST GUMMIHJULSLÆSSERE WG

WG 17E CUMMINS QSB 4.5



HYDRAULISK SYSTEM

Kapacitet: 196 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

Skift alle 2000 timer

ANVEND		KLIMA
Biologisk nedbrydelig olie		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

KØLESYSTEM

Kapacitet: 29 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.