

WERKLUST GUMMIHJULSLÆSSERE WG

WG 35B DAF DNT-620A



MOTOR DAF DNT 620A
Kapacitet: 13 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agri-diesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Synfleet SHPD 10W-40

PRODUKTANBEFALING 3
Dieselfleet LSP Ultra 10W-30

DIFFERENTIALE BAG
Kapacitet: 9,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

DIFFERENTIALE FOR
Kapacitet: 9,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube LS 80W-90

GEAR AUTOMATISK ZF 4WG180 4/3
Kapacitet: 14 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Multifleet SCD 20W-20

WERKLUST GUMMIHJULSLÆSSERE WG

WG 35B DAF DNT-620A



NAVREDUKTIONER BAG

Kapacitet: 4,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

NAVREDUKTIONER FOR

Kapacitet: 4,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

HYDRAULISK SYSTEM

Kapacitet: 150 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

HYDRAULISK BREMSESYSTEM

Kapacitet: 3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Multifleet SCD 10W		

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

WERKLUST GUMMIHJULSLÆSSERE WG

WG 35B DAF DNT-620A



KØLESYSTEM

Kapacitet: 29 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.