

WERKLUST GUMMIHJULSLÆSSERE WG

WG 45C CUMMINS 6BT 8.3C



MOTOR Cummins 6BT8.3C

Kapacitet: 23,8 liter, Filterkapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Skift alle 500 timer

DIFFERENTIALE BAG ZF AP 409 DK

Kapacitet: 15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 100 timer, skift alle 600 timer

DIFFERENTIALE FOR ZF AP 411 DK

Kapacitet: 21 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 100 timer, skift alle 600 timer

GEAR POWERSHIFT ZF 4WG200 4/3

Kapacitet: 16 liter (Servicepåfyldning), Kapacitet: 28 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Skift alle 600 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

ATF Almirol

PRODUKTANBEFALING 2

ATF Dexron II-D

Skift alle 600 timer

WERKLUST GUMMIHJULSLÆSSERE WG

WG 45C CUMMINS 6BT 8.3C



NAVREDUKTIONER BAG

Kapacitet: 5,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 100 timer, skift alle 600 timer

NAVREDUKTIONER FOR

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube LS 80W-90

PRODUKTANBEFALING 3

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 100 timer, skift alle 600 timer

HYDRAULISK SYSTEM

Kapacitet: 160 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus AF 46

Skift alle 2400 timer

ANVEND

Biologisk nedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 2400 timer

WERKLUST GUMMIHJULSLÆSSERE WG

WG 45C CUMMINS 6BT 8.3C



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 2

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 44 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Skift alle 2400 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.