

# WIRTGEN KOLDVASEMASKINER 2000DC

05.20.0059 -> 05.20.0099



**MOTOR** Mercedes-Benz OM442LA  
Kapacitet: 23 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP Ultra 10W-40**

PRODUKTANBEFALING 2

**Agrisynth LSP 10W-40**

PRODUKTANBEFALING 3

**Agridiesel CRD+ 15W-40**

*Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder*

ANVEND  
Første Service

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP Ultra 10W-40**

PRODUKTANBEFALING 2

**Agrisynth LSP 10W-40**

PRODUKTANBEFALING 3

**Agridiesel CRD+ 15W-40**

*Skift alle 50 timer*

**HYDRAULISK SYSTEM**  
Kapacitet: 280 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Perlus H 68**

*Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder*

## SMØREPUNKTER/NIPLER GENERELT

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**MoS2 Grease EP 2**

*Kontroller alle 10 timer*

## SMØREPUNKTER/NIPLER SPECIEL

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

**KØLESYSTEM MOTOR**  
Kapacitet: 80 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

*Kontroller alle 10 timer, skift alle 12 måneder*

# WIRTGEN KOLDVASEMASKINER 2000DC

05.20.0059 -> 05.20.0099



## KØREREDUKTIONSENHED

Kapacitet: 1 liter

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Normal                      |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

Kontroller alle 50 timer, skift alle 500 timer/ 12 måneder

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Første Service              |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

Skift alle 50 timer

## PUMPEFORDELERGEARKASSE

Kapacitet: 4,2 liter

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Normal                      |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

| ANVEND                      |                                    | KLIMA   |
|-----------------------------|------------------------------------|---------|
| Første Service              |                                    | Moderat |
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |         |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |         |

Skift alle 50 timer

## TROMLE SKAL

Kapacitet: 265 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

# WIRTGEN KOLDValsemaskiner 2000DC

## 05.20.0059 -> 05.20.0099



### TROMLEFRÆSERGEARKASSE

Kapacitet: 15 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         |  |  |
|-----------------------------|--|--|
| <b>Abacot MEP Synth 220</b> |  |  |

Kontroller alle 50 timer, skift alle 500 timer/ 12 måneder

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         |  |  |
|-----------------------------|--|--|
| <b>Abacot MEP Synth 220</b> |  |  |

Skift alle 50 timer

### VANDTANKFYLDEPUMPE

Kapacitet: 0,25 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.