

# YALE GAFFELTRUCKS, ELEKTRISKE 4-HJULS ERP 20-30 ALF



## HYDRAULISK SYSTEM

Kapacitet: 27 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**HDX 10W**

*Skift alle 2000 timer/ 12 måneder*

## HYDRAULISK BREMSESYSTEM

Kapacitet: 0,24 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

*Skift alle 6 måneder/ 1200 timer*

## SMØREPUNKTER/NIPLER - HØJTRYKSFITTINGS

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**MoS2 Grease EP 2**

## SMØREPUNKTER/NIPLER ALMINDELIGE OG ANTI-FRIKTIONSLEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**MoS2 Grease EP 2**

## SMØREPUNKTER/NIPLER HJULLEJER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**MoS2 Grease EP 2**

# YALE GAFFELTRUCKS, ELEKTRISKE 4-HJULS ERP 20-30 ALF



## SMØREPUNKTER/NIPLER TELESKOPARM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**MoS2 Grease EP 2**

## HASTIGHEDSREDUKTION

Kapacitet: 3,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 2000 timer/ 12 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*