

YALE GAFFELTRUCKS, LP-GAS/BENZIN GLP 040 RA-JUA MAZDA FE (1981-1982)



MOTOR Mazda FE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

Skift alle 1 måneder/ 200 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

Skift alle 50 timer/ 1 uge

GEAR AUTOMATISK Sumitomo Yale

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 6 måneder/ 1200 timer

GEAR MANUEL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Skift alle 6 måneder/ 1200 timer

NAVREDUKTIONER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 12 måneder/ 2400 timer

YALE GAFFELTRUCKS, LP-GAS/BENZIN

GLP 040 RA-JUA MAZDA FE (1981-1982)



HYDRAULIKSYSTEM SERVOSTYRING

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 46*Skift alle 6 måneder/ 1200 timer*

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Perlus H 22*Skift alle 6 måneder/ 1200 timer*

HYDRAULISK BREMSESYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3*Skift alle 6 måneder/ 1200 timer*

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

SMØREPUNKTER/NIPLER LEJER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.