

YALE GAFFELTRUCKS, LP-GAS/BENZIN GLP 80 VX9 (2010 OG EFTER)



MOTOR GM V8		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Asyntho 5W-30		
<i>Skift alle 500 timer</i>		

DIFFERENTIALE Kapacitet: 6,5 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
<i>Skift alle 2000 timer</i>		

GEAR Kapacitet: 20 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
<i>Skift alle 2000 timer</i>		

NAVREDUKTIONER VÅDE BREMSER Kapacitet: 3,5 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
<i>Skift alle 2000 timer</i>		

HYDRAULISK SYSTEM Kapacitet: 45,8 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		
<i>Skift alle 4000 timer</i>		

YALE GAFFELTRUCKS, LP-GAS/BENZIN GLP 80 VX9 (2010 OG EFTER)

**KØLESYSTEM**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.