

ALFA ROMEO (EU) MONTREAL 105

MONTREAL (1970-1977)

**MOTOR**

Kapacitet: 11 kg (Førstegangsopfyldning), Kapacitet: 8,5 kg (Servicepåfyldning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Multigrade 20W-50*Kontroller alle 500 km, skift alle 12000 km/ 6 måneder***DIFFERENTIALE BAG**

Kapacitet: 2,25 kg

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear ZC 90*Kontroller alle 6000 km, skift alle 18000 km***GEAR MANUEL 5/1**

Kapacitet: 1,6 kg

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Racing Oil 15W-50

PRODUKTANBEFALING 2

Classic Multigrade 10W-30

PRODUKTANBEFALING 3

Classic Monograde 30*Kontroller alle 6000 km, skift alle 18000 km***HYDRAULISK BREMSE- & KOBLINGSSYSTEM**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3*Kontroller alle 6000 km, skift alle 18000 km/ 12 måneder***SMØREPUNKTER/NIPLER HJULLEJER FOR**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 2

MP Lithep Grease EP 2

PRODUKTANBEFALING 3

Multi Purpose Grease 3**SMØREPUNKTER/NIPLER KARDANAKSLENS GLIDESAMLINGER**

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

ALFA ROMEO (EU) MONTREAL 105 MONTREAL (1970-1977)



KØLESYSTEM

Kapacitet: 12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 30000 km/ 12 måneder

STYREHUS

Kapacitet: 0,36 kg

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Classic Gear EP 90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.