ALFA ROMEO (EU) ALFASUD / SPRINT 901, 902, 904 ALFASUD SPRINT 1.5 VELOCE 902A5 (1980-1983)



ENGINE AS30128 Capacity: 4,6 liter (Dry fill), Capacity: 4 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Classic Racing Oil 15W-50				

Change every 10000 km/ 12 months

TRANSAXLE MANUAL 5/1 Capacity: 3,4 liter			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Classic Gear MP 90			
Check every 10000 km/ 12 months, change every 40000 km/ 24 months			

 HYDRAULIC BRAKE/CLUTCH SYSTEM

 use
 CLIMATE

 Normal
 Moderate

 PRODUCT RECOMMENDATION 1
 Image: Climate

 Drauliquid DOT 3
 Image: Climate

 Change every 40000 km/ 12 months
 Image: Climate

WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 7,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.