## ALFA ROMEO (EU) ALFASUD / SPRINT 901, 902, 904 ALFASUD TI 1.5 901G5 (1980-1983)



ENGINE AS30128 Capacity: 4,6 liter (Dry fill), Capacity: 4 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Classic Racing Oil 15W-50				

Change every 10000 km/ 12 months

TRANSAXLE MANUAL 5/1 Capacity: 3,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		
Check evenu 10000 km/ 12 months, change evenu 10000 km/ 21 months		

Check every 10000 km/ 12 months, change every 40000 km/ 24 months

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Change every 40000 km/ 12 months			

WHEEL BEARINGS				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

COOLING SYSTEM Capacity: 7,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.