

AMC JAVELIN JAVELIN 304 V8 (1969-1970)

**ENGINE**

Capacity: 4,7 liter, Filter capacity: 0,95 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 6400 km/ 4 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 6400 km/ 4 months*

USE

Severe

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 1600 km*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30*Change every 1600 km***DIFFERENTIAL REAR**

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 5015*Check every 6400 km***DIFFERENTIAL REAR LIMITED-SLIP** Twin-Grip

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 6400 km*

AMC JAVELIN JAVELIN 304 V8 (1969-1970)

**TRANSMISSION AUTOMATIC 3/1**

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 6400 km***TRANSMISSION MANUAL 3/1**

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Vintage Gear 90*Check every 6400 km***TRANSMISSION MANUAL 4/1**

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Vintage Gear 90*Check every 6400 km***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 6400 km***POWER STEERING**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 6400 km*

AMC JAVELIN JAVELIN 304 V8 (1969-1970)**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 13,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 6400 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.