AMC MATADOR MATADOR 360 V8 (1971-1978)



ENGINE Capacity: 4,7 liter, Filter capacity: 0,95	liter		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 15W-40	Classic Multigrade 10W-30		
Change every 9600 km/ 6 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 15W-40	Classic Multigrade 10W-30		
Change every 4800 km/ 6 months			

DIFFERENTIAL REAR Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Gear MP 90	Gearlube RPC 75W-80	SP Gear 5015
Check every 9600 km	'	'

DIFFERENTIAL REAR LIMITED-SLIP Tw Capacity: 1,9 liter	n-Grip
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear LS 90	
Check every 9600 km	

AMC MATADOR MATADOR 360 V8 (1971-1978)



TRANSMISSION AUTOMATIC 3/1 Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		
Check every 9600 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		
Check every 9600 km, change every 3850	0 km/ 24 months	
TRANSMISSION MANUAL 4/1 Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
Check every 9600 km		

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 9600 km	·

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic ATF A	
Check every 9600 km	·

AMC MATADOR MATADOR 360 V8 (1971-1978)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 12,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Chack avany 0600 km, ahanga ayan	112 months	'	

Check every 9600 km, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.