

AMC MATADOR MATADOR 401 V8 (1971-1978)



ENGINE

Capacity: 4,7 liter, Filter capacity: 0,95 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Change every 9600 km/ 6 months*

USE

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Change every 4800 km/ 6 months*

DIFFERENTIAL REAR

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 5015*Check every 9600 km*

DIFFERENTIAL REAR LIMITED-SLIP Twin-Grip

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 9600 km*

AMC MATADOR MATADOR 401 V8 (1971-1978)



TRANSMISSION AUTOMATIC 3/1

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 9600 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 9600 km, change every 38500 km/ 24 months*

TRANSMISSION MANUAL 4/1

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 9600 km*

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 9600 km*

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 9600 km*

AMC MATADOR MATADOR 401 V8 (1971-1978)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 12,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 9600 km, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.