

AUSTIN-HEALEY 100 100/6 BN4 (1956-1957)**ENGINE**

Capacity: 7,4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|----------------------------------|-----------------------------|--|
| Classic Multigrade 10W-30 | Classic Monograde 30 | |

*Change every 3000 miles/ 4800 km***DIFFERENTIAL REAR**

Capacity: 1,7 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Classic Gear MP 90 | | |

*Change every 6000 miles/ 9600 km***TRANSMISSION MANUAL 4/1**

Capacity: 2,3 liter, Capacity: 3 liter (+ overdrive)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|----------------------------------|-----------------------------|--|
| Classic Multigrade 10W-30 | Classic Monograde 30 | |

*Change every 6000 miles/ 9600 km***HYDRAULIC BRAKE SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Drauliquid DOT 3 | | |

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------------|------------------------------|
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

AUSTIN-HEALEY 100 100/6 BN4 (1956-1957)**COOLING SYSTEM**

Capacity: 10,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26****STEERING BOX****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear MP 90**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.