

AUSTIN A35 A35 (1956-1962)**ENGINE**

Capacity: 3,98 liter, Filter capacity: 0,57 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Classic Multigrade 10W-30***Change every 3000 km***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Monograde 30***Change every 3000 km***DIFFERENTIAL**

Capacity: 1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear EP 90***Check every 1500 km, change every 9000 km***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Classic Gear EP 80***Check every 1500 km, change every 9000 km***TRANSMISSION MANUAL 4/1**

Capacity: 1,33 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Multigrade 10W-30****PRODUCT RECOMMENDATION 2****Classic Monograde 30***Check every 1500 km, change every 9000 km*

AUSTIN A35 A35 (1956-1962)**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 1500 km***GREASE POINTS/NIPPLES**

We are unable to give a standard recommendation for this component. Please contact our service department.

WHEEL BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease*Change every 9000 km***COOLING SYSTEM**

Capacity: 5,4 liter (+ heater), Capacity: 4,93 liter (Without heater)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26**STEERING BOX**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.